



Environment Protection Authority

Waste Levy Guidelines

July 2026



A decorative vertical band on the left side of the page, featuring a series of overlapping Aboriginal patterns. These include a large circular motif with concentric circles and dots, a series of parallel lines, and a pattern of small dots arranged in a grid-like fashion. The colors are various shades of blue and grey.

Acknowledgement of Country

The NSW Environment Protection Authority acknowledges the Traditional Custodians of the land on which we live and work, honours the ancestors and the Elders both past and present and extends that respect to all Aboriginal people.

We recognise Aboriginal peoples' spiritual and cultural connection and inherent right to protect the land, waters, skies and natural resources of NSW. This connection goes deep and has since the Dreaming.

We also acknowledge our Aboriginal and Torres Strait Islander employees who are an integral part of our diverse workforce and recognise the knowledge embedded forever in Aboriginal and Torres Strait Islander custodianship of Country and culture.

Aboriginal artwork by Worimi artist Gerard Black

Contents

Definitions.....	4
Introduction.....	5
1 Waste Levy Guideline 1: Operational purpose	6
1.1 Materials used for roads or other construction works	6
1.2 Materials used for bedding layers	7
2 Waste Levy Guideline 2: Records	8
2.1 General requirements.....	8
2.2 Records for transactions.....	8
2.3 Electronic data capture system	8
2.4 Recording and reporting of trackable liquid waste	9
3 Waste Levy Guideline 3: Waste streams and waste types.....	10
3.1 Waste streams.....	10
Municipal waste.....	10
3.2 Waste types.....	11
4 Waste Levy Guideline 4: Weight conversion factors	13
4.1 Vehicle conversion factors.....	13
4.2 Liquid waste conversion of volume to weight.....	14
5 Waste Levy Guideline 5: Volumetric and topographical surveys for scheduled waste facilities	15
5.1 Landfill facilities: Submitting survey results to EPA.....	15
5.2 Landfill volumetric survey checklist (LVSC).....	16
5.3 Landfill facility information certificate (LFIC).....	17
Stockpile details.....	18
Surveyor's certification.....	18
5.4 Landfill stockpile information and schedule of material movements form.....	19
5.5 Resource recovery facilities: submitting survey results to EPA.....	20
5.6 Resource recovery survey checklist	21
5.7 Resource recovery facility information certificate.....	22
Stockpile volumes and tonnages (if also being calculated as part of the topographical survey).....	22
Surveyor's certification.....	23
6 Waste Guideline 6: Waste and Environment (Liquid Waste) Levy: Technical Guidelines	24

Definitions

The following terms, which are used throughout these Waste Levy Guidelines, have the following meanings. Any other terms, if stated, take the same meaning as in the Protection of the Environment Operations (Waste) Regulation 2014.

EPA means the NSW Environment Protection Authority.

Operational purpose means the purpose for which a waste described in the 'Kind of waste' column of the table in clause 15(1) of the Waste Regulation may be used in order to be eligible for an operational purpose deduction at a scheduled waste facility. The purpose of use for each 'Kind of Waste' is set out in the 'Purpose' column in that table.

EPA's electronic waste tracking system means for each of the circumstance in the table below, the corresponding waste tracking system set out alongside:

Circumstance	Waste tracking system
For waste consigned and received before 28 February 2024	Online Waste Tracking System
For waste consigned before but received on or after 28 February 2024	Online Waste Tracking System
For waste consigned and received on or after 28 February 2024	Integrated Waste Tracking Solution
For waste consigned before 28 February 2024 and the consignment was not properly authorised or tracked in the Online Waste Tracking system before 28 February 2024	Integrated Waste Tracking Solution

Online Waste Tracking System means the Online Waste Tracking System at www.epa.nsw.gov.au/owt/aboutowt.htm.

Integrated Waste Tracking Solution means the Integrated Waste Tracking Solution at <https://www.epa.nsw.gov.au/your-environment/waste/integrated-waste-tracking-solution>.

POEO Act means the *Protection of the Environment Operations Act 1997*.

Waste Regulation means the Protection of the Environment Operations (Waste) Regulation 2014.

Verified weighbridge means a weighbridge that is verified in accordance with the *National Measurement Act 1960* (Cth).

Introduction

These Waste Levy Guidelines contain specific legal requirements which occupiers of scheduled waste facilities must meet in addition to their obligations under the POEO Act and the Waste Regulation.

The Guidelines include how waste is measured to calculate levy liability, when certain levy deductions can be claimed, and how records, surveys and reports are required to be made, kept and provided to the EPA in order for the occupier to fulfil their obligations under the Waste Regulation.

Each Guideline, and the relevant clause(s) of the Waste Regulation under which the Guideline has been made, is listed below.

1. **Waste Levy Guideline 1:** Operational purpose – materials used for roads or other construction works (*Item 2 of the Table in clause 15(1) of the Waste Regulation*) and bedding layers (*Item 10 of the Table in clause 15(1) of the Waste Regulation*)
2. **Waste Levy Guideline 2:** Records (*clauses 32, 33(a), 34, 36(3)(g) of the Waste Regulation*)
3. **Waste Levy Guideline 3:** Waste streams and waste types (*clauses 22(2)(b), 26(1)–(2), 27(a), 28(a), 30(a) and 31(1)–(2) of the Waste Regulation*)
4. **Waste Levy Guideline 4:** Weight conversion factors (*clauses 5(b), 36(3)(d)(ii), 36(4) and 38 of the Waste Regulation*)
5. **Waste Levy Guideline 5:** Volumetric and Topographical surveys for scheduled waste facilities (*clauses 23(1)–(2) and 24(1)(b) and 33 of the Waste Regulation*)
6. **Waste Levy Guideline 6:** Waste and environment (liquid waste) levy: Technical Guidelines (*clause 17(b) of the Waste Regulation*).

These Waste Levy Guidelines take effect on and from 24 July 2025 and replace the previously gazetted EPA Waste Levy Guidelines (NSW Government Gazette No 64 of 28 February 2024, pages 14–39).

1 Waste Levy Guideline 1: Operational purpose

1.1 Materials used for roads or other construction works

See Item 2 of the Table in clause 15(1) of the Waste Regulation.

An occupier of a scheduled waste facility may apply to the EPA for approval to use at the facility any waste received from off-site for the purpose of roads or other construction works of a kind specified in these Guidelines.

The other kinds of construction works which an operator may apply for approval to use are: application of materials to land as foundational supports (e.g. hardstands, building foundations and infrastructure support).

Materials that are to be used for the purpose of roads or other construction works at the facility must meet the specifications contained in Table 1. Applications to seek the EPA's approval to use these materials for an operational purpose must be accompanied by supporting details from a **professional engineer**** certifying that the materials and works subject of the claim:

- conform to recognised engineering standards, and
- are necessary for the proper functioning of the facility.

The occupier may then claim a deduction from the waste levy for any waste the occupier uses in accordance with the approval granted by the EPA in accordance with clause 15(4)–(6) of the Waste Regulation for the Operational Purpose.

Table 1 Specifications

Operational purpose	Specifications
Roads	1. Virgin Excavated Natural Materials (VENM); or Excavated Natural Materials (ENM), that meet the requirements for the supply of excavated natural materials under the ENM Order*; OR 2. Recycled road base (base course and sub-base road making materials) that meets the requirements for the supply of 'recovered aggregate' under the Recovered Aggregate Order* These materials may only be used for roads which have a wearing surface.
Construction works	1. Virgin Excavated Natural Materials (VENM); or Excavated Natural Materials (ENM), that meet the requirements for the supply of excavated natural materials under the ENM Order*; OR 2. Recycled road base (base course and sub-base road making materials) that meets the requirements for the supply of 'recovered aggregate' under the Recovered Aggregate Order*

* The Recovered Aggregate Order means the Recovered Aggregate Order 2014 (as in force from time to time) issued by the EPA; the ENM Order means the Excavated Natural Materials Order 2014 (as in force from time to time) issued by the EPA. The current versions of these Orders are published on the EPA's website at <http://www.epa.nsw.gov.au/wasteregulation/orders-exemptions.htm>.

**A professional engineer is one that holds appropriate and relevant accreditation, or registration as a Chartered Professional Engineer (CPEng) with Engineers Australia, or a Registered Professional Engineer of Professionals Australia (RPEng).

1.2 Materials used for bedding layers

See Item 10 in the Table in clause 15(1) of the Waste Regulation.

An occupier of a scheduled waste facility may apply to the EPA for approval to use at the facility any waste received from off-site for the purpose of bedding layers to protect landfill lining systems if the layers are of a kind specified in these Guidelines.

Materials that are to be used for the purpose of bedding layers at the facility must meet the specifications contained in Table 2.

The occupier may then claim a deduction from the waste levy for any waste the occupier uses in accordance with the approval granted by the EPA in accordance with clause 15(4)–(6) of the Waste Regulation for the Operational Purpose.

Table 2 Specifications

Operational purpose	Specifications
Bedding Layers	The material must, at the time it is received at the facility: 1. Be fine particulate matter (being sand or such other material expressly authorised in the environment protection licence held by the occupier to be used for the operational purpose of a bedding layer) having a thickness not greater than 150 mm; 2. Have adequate thickness, particle size distribution, permeability, internal shear strength and interface friction with adjacent layers; 3. Protect the geonet drainage geocomposite by providing an overlying padding or protection layer.

2 Waste Levy Guideline 2: Records

See clauses 32, 33(a), 34 and 36(3)(g) of the Waste Regulation.

This Guideline sets out how an occupier of a facility must record, keep and provide to the EPA (where relevant) information required to be recorded under Part 3 of the Waste Regulation.

2.1 General requirements

Each occupier of a scheduled waste facility must ensure for all information required to be recorded under Part 3 of the Waste Regulation that:

- the original records of the information (such as paper documents) are retained and are accessible by the EPA in their original form
 - all record-keeping systems are designed so that details of any adjustments to records are recorded against the adjusted record, including that the record has been amended and the extent of the change
 - all electronic records are backed up weekly and the back-up records are stored in a secure location
 - quantity of waste is recorded to two decimal places (e.g. 14.22 tonnes)
 - all electronic records are able to be downloaded by the EPA in an .xls, .xlsx, .csv or .dbf format at any time.
-

2.2 Records for transactions

For each vehicle entry (transaction) into a scheduled waste facility, records must be kept in a manner that is exportable, copyable and accessible by the EPA in spreadsheet form. Records must display all information required to be recorded under clauses 27–30 and 32 of the Waste Regulation for each transaction. Each field for a transaction (e.g. date, weight, vehicle registration number) must be displayed as a heading in the first row and the content required for that field set out below that heading.

2.3 Electronic data capture system

For facilities with data capture software connected to a verified weighbridge ('electronic data capture system'), all of the information required to be recorded under clauses 27–30 of the Waste Regulation must be recorded into the electronic data capture system unless:

- the weighbridge is out of operation, or
- the electronic data capture system malfunctions whilst the weighbridge continues to operate.

In these circumstances, the information required to be recorded for a transaction must be manually recorded and entered into the electronic data capture system as soon as the system resumes operation (with details confirming that the original recording was manual).

2.4 Recording and reporting of trackable liquid waste

Scheduled waste facilities receiving or consigning trackable liquid waste must use the EPA's electronic waste tracking system (or an alternative system approved by the EPA in writing) to record and provide the information required under Part 3 of the Waste Regulation for trackable liquid waste. Scheduled waste facilities receiving trackable liquid waste must also maintain original records of the information required under Part 3 of the Waste Regulation for:

- trackable liquid waste and other material received at the facility
- trackable liquid waste and other material stored at the facility
- trackable liquid waste transported from the facility
- waste and material other than trackable liquid waste transported from the facility.

Sections 2.2 and 2.3 of this Waste Levy Guideline 2 do not apply to scheduled waste facilities which only have levy liability in relation to trackable liquid waste.

3 Waste Levy Guideline 3: Waste streams and waste types

See clauses 22(2)(b), 26(1)–(2), 27(a), 28(a), 30(a) and 31(1)–(2) of the Waste Regulation.

The Waste Regulation requires that occupiers of scheduled waste facilities keep records, and report on waste streams and waste types received at, stockpiled on or sent from their facility in certain circumstances. The waste streams and waste types are determined in accordance with the Waste Levy Guidelines. This Guideline sets out what information must be recorded and reported.

3.1 Waste streams

Under clause 27(a) and 28(a) the occupier of a scheduled waste facility must record waste as one of the following three waste streams:

- **Municipal waste** consists of one or more of the following waste types: domestic waste, other domestic waste, council waste, or garden organics (as those terms are defined in 3.1.1 below).
- **Commercial and industrial waste** includes waste generated by businesses (including shopping centres), industries, schools, hospitals, other institutions, or government offices.
- **Construction and demolition waste** is generated from construction or demolition works, and includes asphalt waste or excavated natural material.
- **Other** if it is not possible to identify whether the waste is municipal waste, commercial and industrial waste or construction and demolition waste.

Municipal waste

Where municipal waste is recorded as the waste stream, the occupier must also record the municipal waste sub-stream in accordance with the following list:

- domestic waste – household waste (other than garden organics) collected by or on behalf of a council as part of a routine kerbside service carried out at least once per fortnight
- other domestic waste – household waste (other than garden organics or domestic waste) collected by or on behalf of a council or taken directly to the waste facility by or on behalf of the householder
- council waste – waste (other than garden organics) collected by or on behalf of a council from parks or gardens, council street bins, the sweeping of streets by or on behalf of the council, council waste drop-off centres and major public events
- garden organics – waste consisting of plants or parts of plants, including compost or mulch.

3.2 Waste types

Table 3 lists waste types, including the corresponding Code for the purposes of the record-keeping requirements under clauses 27(a), 28(a), 31(1)–(2) and the Waste Contributions Monthly Report (clause 22(2)(b)).

Table 3 Waste types

Description of waste	Code
Aggregate, road base or ballast	AGG
Aluminium (non-ferrous)	AL
Asbestos (N220)	ASB
Asbestos contaminated soil	ASBSOIL
Ashes	ASH
Asphalt	ASPH
Batteries	BATT
Bentonite	BENT
Biosolids or manures	BIO
Bricks or concrete	BC
Ceramics, tiles, pottery	CER
Coal washery rejects	CWR
Commingled recyclables	COMM
Composts or mulches	COMP
Contaminated soil	CONT
Dredging spoil	DSP
E-waste	EWASTE
Excavated Natural Material	ENM
Ferrous (iron or steel)	FE
Food organics+	FO
Food organics and garden organics	FOGO
Garden Organics#	GO
Glass	GLASS
Liquid waste	LIQUID
Mattresses	MATT
Mixed waste*	MIX
Mixed waste organic output	MWOO
Non-ferrous (metals, not iron, steel or aluminium)	NFE
Oil	OIL
Paper or cardboard	PAPER
Pharmacy or clinical	PHARM
Plasterboard	PB

Description of waste	Code
Plastic	PL
Potential acid sulphate soils	PASS
Problem waste	PROB
Recovered Fines as Alternative Daily Cover	RFADC
Residues or rejects	RES
Shredder floc	FLOC
Soil (not contaminated or VENM)	SOIL
Solar PV systems	SOLAR
Textiles, rags	TEXT
Tyres	TYRE
Veterinary waste	VET
Virgin excavated natural material	VENM
Woods, trees or timber	WOOD

* For loads which contain more than one waste type, the 'description of waste' and 'code' should be mixed waste and MIX respectively.

+ FO - Food Organics has replaced FOOD – Food and Kitchen as a waste type code

GO - Garden Organics has replaced VEG – Vegetation or garden as a waste type code

The waste types that are required to be recorded under clause 30 for wastes that are used for an operational purpose at a scheduled waste facility are listed in the table in clause 15(1) under the column 'Kind of waste'.

If the EPA approves the use of waste for an operational purpose, the EPA will advise when it issues the approval:

- if the waste type is required to be reported in the Waste Contributions Monthly Report (WCMR), and
- the appropriate Code (if any) for recording and reporting in the WCMR.

4 Waste Levy Guideline 4: Weight conversion factors

See clauses 5(b), 36(3)(d)(ii), 36(4) and 38 of the Waste Regulation.

An occupier of a scheduled waste facility is required to measure the quantity of waste that is transported into or out of the facility. This Guideline sets out when conversion factors can be used to measure the quantity of waste.

4.1 Vehicle conversion factors

Vehicle conversion factors may only be used by the occupier of a scheduled waste facility who is required under the Waste Regulation to install a weighbridge if:

- the verified weighbridge at a scheduled waste facility is out of operation; or
- the EPA has specifically exempted or deferred the occupier from the requirement to install a verified weighbridge under the Waste Regulation, and if an alternative measuring system has not been prescribed in the notice of exemption or deferral.

In these circumstances operators must use the conversion factors listed in Table 4 to measure the quantity of a load of waste or other material transported into or out of the waste facility, for the specified type of vehicle or bin in which the waste is transported.

Table 4 Vehicle and bin weight conversion factors

Sources			
	Municipal, Commercial and Industrial waste	Construction and Demolition waste	Sand, soil or soil like material including clay, rock, stone or similar quarried materials
	Deemed tonnage (or t/m ³ if stated of load)	Deemed tonnage (or t/m ³ if stated of load)	Deemed tonnage (or t/m ³ if stated of load)
Open truck			
Single rear axle with two rear wheels or four small rear wheels	0.62	0.98	2.47
Single rear axle with four normal size wheels	1.16	2.76	5.58
Tandem rear axle (bogie drive)	3.74	7.14	10.97
Twin steer with twin rear axles	5.57	7.61	10.97
Tipping semi-trailer	5.79	15	15
Skip bin			
	0.8 (t/m ³)*	Mixed waste: 0.7 (t/m ³) Segregated concrete or brick: 1.2 (t/m ³)	1.5 (t/m ³)*

	Crushed concrete and brick base material: 1.5 (t/m ³) Crushed aggregate: 1.3 (t/m ³) All other waste: 1.1 (t/m ³)*
Enclosed trucks, compactors, trucks and dogs, B-doubles	All sources Deemed tonnage
Single steer with single rear axle	2.72
Single steer with tandem rear axle	6.38
Tandem rear axle (bogie drive) with trailer (truck and dog)	29.1
Twin steer with tandem rear axle	7.96
Waste transfer truck (Walking floor)	19.89
B-double	39.3
Small vehicles and mobile garbage bins (all sizes)	
Car/station wagon	0.06
Van/ute/trailer	0.3
Mobile garbage bin (as used for normal domestic kerbside collections: all sizes)	0.06 per bin**

* The total deemed weight of a load in a skip bin is to be determined based on bin size, not amount of waste or material in the bin.

** If more than six mobile garbage bins are delivered in a ute or trailer, the maximum deemed weight is 0.3 tonnes: that is the standard conversion factor applying to utes and trailers.

NOTE: The above conversion factors for specified vehicles apply to each load of waste or material in the vehicle, regardless of how full.

4.2 Liquid waste conversion of volume to weight

For the purposes of clause 5(b) of the Waste Regulation, one kilolitre of liquid waste that is measured by volume is taken to weigh one tonne.

5 Waste Levy Guideline 5: Volumetric and topographical surveys for scheduled waste facilities

See clauses 23(1)–(2), 24(1)(b) and 33 of the Waste Regulation.

An occupier of a scheduled waste facility is required to provide results of a topographical or volumetric survey in an approved form and manner specified by the Waste Levy Guidelines. This Guideline sets out how the results must be provided.

Sections 5.1–5.4 apply to any scheduled waste disposal facility that is a landfill site.

Sections 5.5–5.7 apply to any scheduled waste facility other than a scheduled waste disposal facility that is a landfill site.

5.1 Landfill facilities: Submitting survey results to EPA

Any results from a survey required must be submitted to EPA by completing all three of the:

- Landfill Survey Checklist set out in section 5.2
- Landfill Facility Information Certificate set out in section 5.3
- Stockpile Information and Schedule of Material Movements Form set out in section 5.4.

The completed documents must be submitted together with the survey plan of the facility in electronic format (e.g. .dwg, .xls, .xlsx, .pdf) to:

wastelevy.compliance@epa.nsw.gov.au

OR

by mail to the following address:

Waste Levy Compliance Unit

Environment Protection Authority

Locked Bag 5022

PARRAMATTA NSW 2124

Note: Guidance as to the meaning of key terms used in sections 5.2 to 5.4 can be found on the EPA website at [Volumetric Survey Definitions](#). These definitions should be referred to when completing these documents.

5.2 Landfill volumetric survey checklist (LVSC)

Facility:
Licence number:
Survey period:
Date of survey:

Survey item	Yes
Survey to be carried out by a qualified surveyor as defined in Clause 7 of the Protection of the Environment Operations (Waste) Regulation 2014.	
Survey results are presented in the form of a survey plan. The survey plan shows survey results to the licensed boundaries of the facility at the time of the survey.	
Terrain levels are represented on the survey plan by contours at not more than one metre intervals.	
All levels are related to Australian Height Datum and the origin of levels noted on the survey plan.	
Spot levels are taken at sufficient frequency to allow interpolation of levels from the survey plan to ± 0.2 metres at the 90% confidence level.	
Boundaries of the site, date of survey, adjoining title information, scale bar, buildings, roads, fences, ponds, landfill cell extraction areas, weighbridges, settlement, subsidence and any other significant details that will likely impact on the volume usage are noted on the survey plan.	
The boundaries of all active cells which received waste during the survey period are noted on the survey plan by use of the Map Grid of Australia 1994 (MGA94).	
The boundaries of all cells which are currently being excavated, mined or quarried for any purpose are noted on the survey plan by use of the Map Grid of Australia 1994 (MGA94).	
All changes in the volume in the active cells and any other area on the facility during the survey period are noted on the survey plan and listed in the Landfill Facility Information Certificate (Form 5.3).	
Stockpile locations are clearly noted on the survey plan and provided with an identification number that correlates with the Landfill Facility Information Certificate (Form 5.3) and Landfill Stockpile Information Form (Form 5.4).	

Signed:	_____
Date:	_____
Name (surveyor):	_____
Organisation:	_____

5.3 Landfill facility information certificate (LFIC)

Licence no:	
Survey period:	
Date of survey:	
Facility name:	
Facility address:	
Occupiers name:	
Site area (hectares):	
Title details:	
Lot:	D.P
Lot:	D.P
Lot:	D.P
Lot:	D.P

Note: The MGA94 coordinates of licensed boundaries, all active cells, all excavated areas and all subsidence areas must be shown on the survey plan.

Total licensed area (hectares)
Date of survey
Total landfill design capacity (m³) <i>Tool tip – Total landfill design capacity is the total planned landfill volume that has been approved by the consenting authority for the entire site. This space may not actually exist at present and may be dependent upon planned construction of future landfill cells for waste disposal.</i>
Total void space remaining in the active cell(s) (m³) at the date of this survey* <i>Tool tip – An active cell is one that either received waste for landfilling and/or was mined or quarried during the survey period.</i> <i>This figure is different from the "total landfill design capacity remaining" unless your facility has only one cell.</i>
Total void space consumed in the active cell(s) during the 6-month survey period (m³) <i>Tool tip – This is the total volume consumed (m³) during the 6-month survey period by the burial of waste (which includes daily cover) in the cell(s) that were active during the survey period.</i>
Total landfill design capacity remaining (m³) at the date of this survey <i>Tool tip – This is the total landfill design capacity less total void space consumed since the landfill started operating.</i> <i>This is different from the "total void space remaining in the active cell" unless your facility has only one cell.</i>

Average estimated compaction rate during the 6-month survey period (tonnes/m³)

Tool tip – Total amount of waste landfilled onsite (refer to Schedule of Material Movements) divided by total void space consumed in the active cell(s) during the 6-month survey period.

* If more than one active cell during survey period, provide individual volumes (m³) on survey plan using a text box.

Stockpile details

Stockpile identification	Volume (m ³)

If space is insufficient, please attach a separate schedule or insert rows in the Microsoft Excel version of this form. The surveyor should sign the Schedule (see next page).

Surveyor's certification

I, _____ (full name)

a qualified

surveyor, of*

*(must provide company name and include relevant ABN or ACN)

certify that the above information is correct and that the survey and computations represented in the attached survey plans have been conducted in accordance with the approved form and manner requirements of the Protection of the Environment Operations (Waste) Regulation 2014.

Signature

Date

5.4 Landfill stockpile information and schedule of material movements form

Facility:
Licence number:
Survey period:
Date of survey:

Stockpile ID on volumetric survey ¹	Stockpile information					
	Material type (using WCMR ² codes)	Volume in m ³	Density value in t/m ³	Weight in tonnes	Stockpile won on site – Yes/No	Applicable financial year for levy rate

¹ Please ensure that the Stockpile ID order is the same as that given in Form 5.3

² WCMR = Waste contribution monthly report

Schedule of material movements
Total amount of material landfilled on site during the 6-month survey period (tonnes) <i>Tool tip – This is the total amount of waste that has been disposed of or buried in the active cell(s) during the 6-month survey period. This includes the amount of waste used for daily cover.</i>
Total amount of material won on site during the 6-month survey period (tonnes) <i>Tool tip – Total amount of material during the 6-month survey period that has been excavated from on-site and has either been stockpiled for reuse on-site or transported offsite for disposal, resource recovery or reuse.</i>
Total amount of material received for an operational purpose during the 6-month survey period (tonnes). <i>Tool tip – This is the total amount of waste received during the 6-month survey period that has been received at the facility for an operational purpose, whether or not the use is subject to an EPA approval (DIN) or retrospective claim (do not include ‘record and not report’ items).</i>

Signature	Date
Name (position)	Of (licensee)

5.5 Resource recovery facilities: submitting survey results to EPA

Any results from a survey required must be submitted to EPA by completing the:

- Resource Recovery Survey Checklist set out in section 5.7,
- Resource Recovery Facility Information Certificate set out in section 5.8.

The completed documents must be submitted together with the survey plan of the facility in electronic format (e.g. .dwg, .xls, .xlsx, .pdf) to:

wastelevy.compliance@epa.nsw.gov.au

OR

by mail to the following address:

Waste Levy Compliance Unit

Environment Protection Authority

Locked Bag 5022

PARRAMATTA NSW 2124

Note: Guidance as to the meaning of key terms used in sections 5.6 and 5.7 can be found on the EPA website at [Volumetric Survey Definitions](#). These definitions should be referred to when completing these documents.

5.6 Resource recovery survey checklist

Facility:
Facility address:
Occupier's name:
Licence number (if applicable):
Survey period:
Date of survey:

Survey item	Yes
Survey to be carried out by a qualified surveyor as defined in Clause 7 of the Protection of the Environment Operations (Waste) Regulation 2014.	
Survey results must be presented in the form of a topographical plan. The survey plan must show survey results to the licensed boundaries of the Facility. In the case of an unlicensed facility, the survey plan must show survey results to the legal boundaries of the Facility.	
Terrain levels must be represented on the survey plan by contours at not more than one metre intervals.	
All levels must be related to Australian Height Datum and the origin of levels noted on the survey plan.	
Spot levels must be taken at sufficient frequency to allow interpolation of levels from the survey plan to ± 0.2 metres at the 90% confidence level.	
Boundaries of the site, date of survey, adjoining title information, scale bar, buildings, roads, fences, ponds, and weighbridges must be noted on the survey plan.	
Stockpile locations must be clearly noted on the survey plan and provided with an identification number that correlates with the Facility Information Certificate below.	

Signed:	_____
Date:	_____
Name (surveyor):	_____
Organisation:	_____

5.7 Resource recovery facility information certificate

Facility name:	
Facility address:	
Occupier's name:	
Licence number (if applicable):	
Survey period:	
Date of survey:	
Site area (hectares):	
Title details:	
Lot:	D.P
Lot:	D.P
Lot:	D.P
Lot:	D.P
Map Grid Australia (MGA) coordinates of licensed or legal boundaries (show on plan)	

Stockpile volumes and tonnages (if also being calculated as part of the topographical survey)

Stockpile identification	Volume (m ³)	Density value (t/m ³)	Derived tonnage(s)

If space is insufficient, attach a separate schedule or insert rows in the Microsoft Excel version of this form. The surveyor should sign the schedule (see next page).

Surveyor’s certification

I, _____ (full name)

a qualified
surveyor, of*

*(must provide company name and include relevant ABN or ACN)

certify that the above information is correct and that the survey and computations represented in the attached survey plans have been conducted in accordance with the approved form and manner requirements of the Protection of the Environment Operations (Waste) Regulation 2014.

Signature _____ Date _____

6 Waste Guideline 6: Waste and Environment (Liquid Waste) Levy: Technical Guidelines

See clause 17(b) of the Waste Regulation.

The occupier of a scheduled waste facility who is required to pay the waste levy may deduct from the levy payable an amount in respect of trackable liquid waste received at the facility which is transported from the facility as a substance other than trackable liquid waste to a place for lawful recycling, re-use or processing, but only if any requirements of the Waste Levy Guidelines have been satisfied.

For the purpose of clause 17(b), the requirements in each row of Column 3 of Table 5 apply in relation to the type of substance described in Column 1 that is transported to a place for the purpose in Column 2.

Table 5 Requirements

Column 1 Substance	Column 2 Purpose	Column 3 Requirements
The liquid component of processed, treated or recycled trackable liquid waste.	Lawful recycling, re-use or processing as industrial water in a commercial or industrial process.	The liquid component must comply with relevant industrial specifications, standards and guidelines for the particular commercial or industrial process. Where a specification is not available or applicable, a risk management plan must be undertaken (and made available to the EPA) consistent with the principles outlined in the National Guidelines for Water Recycling: Managing Health and Environmental Risks (2006) ¹
The aqueous liquid component of processed, treated or recycled trackable liquid waste.	Lawful ² recycling, re-use or processing in the irrigation of agricultural land or public parks or other recreational facilities.	The aqueous fraction of treated or processed liquid waste must be of a quality appropriate for irrigation on agricultural land or application to land without causing harm to the environment or human health. The water quality of the aqueous fraction must not exceed the trigger values for the specific physical, chemical and biological parameters outlined in: 1. The Australian and New Zealand Guidelines for Fresh and Marine Water Quality (2000), Chapter 4: Primary

¹ Environment Protection and Heritage Council, Natural Resource Management Ministerial Council, Australian Health Ministers' Conference 2006, *National Water Quality Management Strategy: Australian Guidelines for Water Recycling: Managing Health and Environmental Risks (Phase 1)*, EPHC, NRMCMC, AHMC.

² Any application of the substance to land must comply with any applicable resource recovery order and exemption. The current versions of orders and exemptions are published on the EPA's website at <http://www.epa.nsw.gov.au/wasteregulation/orders-exemptions.htm>. Where no resource recovery order or resource recovery exemption is currently available for the intended use of a waste material, an application can be made to the EPA: see <https://www.epa.nsw.gov.au/your-environment/recycling-and-reuse/resource-recovery-framework/apply-for-an-order-and-exemption>.

Industries, Sections 4.2.1–4.2.9 Water Quality for Irrigation (the ANZECC Guidelines). ³		
2. The ‘health’ guideline values in the Australian Drinking Water Guidelines (2011), ⁴ Chapter 10: Monitoring for Specific Characteristics in Drinking Water. ⁵		
The solid or liquid component of processed, treated or recycled trackable liquid waste which has been recovered into its original substance (e.g. solvent, chemical, fuel or oil) (Original Form)	Lawful recycling, re-use or processing (other than application to land) in the substance’s Original Form	The solid or liquid component must be sent off-site for re-use in its Original Form and must comply with relevant legislation, specifications, standards and guidelines for the proposed re-use.

³ Australia and New Zealand Environment and Conservation Council, Agriculture and Resource Management Council of Australia and New Zealand 2000, *Australian and New Zealand Guidelines for Fresh and Marine Water Quality*, ANZECC, ARMCANZ.

⁴ National Health and Medical Research Council, Natural Resource Management Ministerial Council 2011, *National Water Quality Management Strategy: Australian Drinking Water Guidelines 6 2011*, NHMRC, NRM.

⁵ Where no appropriate guideline values are available for identified chemicals or where the waste contains greater than trace amounts of substances, such as heavy metals, solvents, chlorinated organic compounds, agricultural chemical residues or petrochemicals, the waste in question is generally not suitable for application to land for irrigation purposes.



Published by NSW Environment
Protection Authority

Visit:
6 Parramatta Square
10 Darcy Street
Parramatta NSW 2150

Mail:
Locked Bag 5022,
Parramatta NSW 2124

Phone:
+61 2 9995 5000 (switchboard)

TTY users:
Phone 133 677, then ask for 131 555

Speak and listen users:
Phone 1300 555 727, then ask for 131 555

Email:
info@epa.nsw.gov.au

Website:
epa.nsw.gov.au

Report pollution and
environmental incidents

Environment Line:
131 555 (NSW only) or
info@epa.nsw.gov.au

ISBN 978 1 923328 64 8
EPA 2026P4689
July 2026

© 2026 State of NSW and the NSW
Environment Protection Authority

With the exception of photographs, the
State of NSW and the NSW Environment
Protection Authority (EPA) are pleased to
allow this material to be reproduced in
whole or in part for educational and non-
commercial use, provided the meaning is
unchanged and its source, publisher and
authorship are acknowledged. Specific
permission is required for the reproduction
of photographs.

All content in this publication is owned by
the EPA and is protected by Crown
Copyright, unless credited otherwise. It is
licensed under the Creative Commons
Attribution 4.0 International (CC BY 4.0),
subject to the exemptions contained in the
licence. The legal code for the licence is
available at Creative Commons.

The EPA asserts the right to be attributed as
author of the original material in the
following manner: © State of New South
Wales and the NSW Environment Protection
Authority 2026.